

# PVC Transparent Soft And Rigid Sheet Extrusion Line

## PVC透明软/硬片生产线

### PVC Transparent Rigid Sheet Extrusion Line

PVC transparent sheet have many advantages of fire-resistance, high quality, low cost, high transparent, good surface, no spot, less water wave, high strike resistance, easy to mould and etc. it applies to different kinds of packing, vacuuming and case, such as tools, toys, electrics, food, medicine and clothes.

### PVC挤出透明硬片生产线

PVC挤出透明片材具有阻燃自熄、质优价廉、透明度高、表面光泽好、晶点少、水纹小、耐冲击性强且易于成型等特点，广泛应用于各类工具、玩具、电子、食品、医药、服装等行业的吸塑、折盒、包装等。



### PVC Transparent Soft Sheet Extrusion Line

PVC transparent soft sheet is product instead of the traditional door curtain. It is soft, clear, insulation, safe, environmental protection, acid resistance, no peculiar smell, easy to clean, and etc, also can be used in cold and heat insulation, save energy, wind-proof, keep humidity, anti-corruption, fire proof, anti static, ultraviolet radiation proof, sound proof, table pad, daylighting, industrial damping, safety warning, protect surface, these application used in refrigeration, foodstuff, printing, weaving, electrics, instrument, medicine, storage. It has good effect on insulation for electricity, and harmful light.

### PVC挤出透明软片生产线

PVC透明软板软门帘是传统棉门帘的换代产品。本产品具有柔软、透明、绝缘、安全、绿色、环保、耐酸碱、无异味、易清洗等特点，能够保冷、保温、节能、防尘、防风、保湿、防腐、防火、防静电、防强光、防紫外线、隔音、桌垫、采光、工业减振、安全警示、铺地面墙面、器物表面防护和漆膜保护，可用于冷冻、食品、印刷、纺织、电子、仪表、制药、仓储、商场等场所。对带电作业场所的绝缘，有害弧光的遮挡，均起到很好的效果。



### 主要技术参数：Main Technical Specification

机型 Model	GWP120/21-1500	GWC80/156-1220
制品宽度 Products Width	1400mm	1220mm
制品厚度 Products Thickness	0.3-1.5mm	0.5-3mm
挤出机规格 Extruder Specification	GWP120/21	GWC80/156
主电机功率 Main Motor Power	90KW	75KW
设计挤出产量 Designed Extrusion Output	350KG/H	300KG/H

备注：以上规格参数如有变更，恕不另行通知。Note: The specifications are subject to change without prior notice.